

thalassa sensation

54" x 54" x 20"



Product No.

Model	TMU BTHACD00T-XX	Soaker BTHACD00N-XX
-------	------------------	---------------------

ThermoMasseur (TMU)

Air Jet System	\$5,355
Jets	40
1 heated backrest & headrest	Included
Mia® Control	Included
BU-Touch Control Application BUTOUCH	\$520
Geysair®	Included
AromaCloud®** BAROMAC	\$620
Illuzio Chromatherapy BCHRO6	\$1,045
2nd heated backrest (WTS-1 zone) BSHB	\$1,180

Soaker

AromaCloud®** BAROMAC	\$620
Illuzio Chromatherapy BCHRO6	\$1,045
WarmTouchShell® BWTS	\$1,180
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$390

Features

Installation Type	Drop-in & Corner
No. of bathers ♀♂ Imp. gallons 46 US gallons 55 Grab bars (color match) 1	
Standard Bath Color	
☐ White 01 ☐ Biscuit 02	Included

Options UPCHARGE APPLICABLE

Control (TMU only)	
MiaPlus®# BMIAP1-XX	\$300
Skirt SJ-3 SE BSJ3-XX	
☐ White 01 ☐ Biscuit 02	\$1,515
Clear Acrylic Grab Bars BGBG10-XX	
☐ Chrome 07 or ☐ Brushed Nickel 09 inserts	\$65
Tile Flange	
Ordered with bath (not installed) BTILEN	\$85
Factory-installed. Front BTILEF. Special installation BTILEO	\$165
Bath Pillow BPILLOW	\$250
	16" x 35" BOVER16-XX
Drain & Overflow	
☐ Chrome 07	\$275
☐ White 01 ☐ Biscuit 02	\$305
☐ Brushed Nickel 09	\$420
☐ Polished Nickel 10	\$420
☐ Oil-rubbed Bronze 11	\$420
If Required by Construction Code	
16" x 35" Cable driven brass drain & overflow kit BOVERBR	\$250


** The AromaCloud® is built into the deck (factory installed).
The MiaPlus® Control is Included when purchasing Chromatherapy and/or a 2nd heated backrest on a TMU.
+++ Only when ordering an AromaFlow, a ZenFlow is mandatory (Upcharge). Specify the finish of the drain.

thalassa sensation

54" x 54" x 20"



Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	10 ½"
B	Outside edge to overflow	5 ½"
C	Total length	58 ⅞"
D	Total width	75 ⅞"
E	Bathing well length	44"
F	Bathing well width	28 ⅞"
G	Sidewall length	53 ⅞"
H	Deck width (widest point)	5 ¼"
I	Total height to raised headrest	22 ¼"
J	Height from bottom of bath to top deck	20 ¼"
K	Height from bottom of bath to bottom of deck	18 ¾"
L	Height from bottom of drain to center of overflow	15 ¾"
M	Maximum water level (Drain & overflow 16" x 35")	14"
N	Slope of backrests	21°

A AromaCloud® position **T** Turbine position (TMU) **W** Indicates WarmTouchShell® position (Soaker)
C Control position when factory-installed (Mia® or DOT) **H** Indicates heated backrest (TMU)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A, 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A, 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access). Optional tile flange.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000014
Approx. shipping weight	135 lb
Turbine power	550 W
Air heater	600 W

Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ±0.25" (±0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.