amma 6036

60" x 36" x 21"



Product No.

Model	TMU BAMFRBOOT-XX	Soaker BAMFRB00N-XX

ThermoMasseur (TMU)

Air Jet System	\$7,830
Jets	45
1 heated backrest & headrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$520
Geysair®	Included
AromaCloud®** BAROMAC	\$620
Illuzio Chromatherapy BCHRO6	\$1,045

Soaker	\$4,685
AromaCloud®** BAROMAC	\$620
Illuzio Chromatherapy BCHRO6	\$1,045
WarmTouchShell® BWTS	\$1,180
DOT Control	Included with therapy

Features

Catalos	
Installation Type	Drop-in & Alcove (3 walls)
No. of bathers Imp. gallons 41 US gallons 50 Inverted V 1 Armrests 2 Grab bars (Color match	
Standard Bath Color	
White 01 Biscuit 02	Included

Options UPCHARGE APPLICABLE

Skirt	BSMUL-XX	Multifit BSJ1-XX	SJ-1
White 01 Biscuit 02		\$730	\$750
Clear Acrylic Grab Bars BGBG10-XX			
Chrome 07 Brushed Nickel 09 inse	erts	\$65	
Tile Flange (specify right or left)			
Ordered with bath (not installed) BTILEN		\$85	
Factory-installed. Right BTILER, Left BTILEL, Special installation BTILEO		\$165	
Bath Pillow BPILLOW		\$250	
Drain & Overflow	Integrated ZenFlow [†] BOVERINZF-XX	Integrated with trim BOVERIN-XX	16" x 35" BOVER16-XX
Chrome 07	\$215	\$245	\$275
White 01 Biscuit 02	\$175	\$215	\$305
Brushed Nickel 09	\$215	\$245	\$305
Polished Nickel 10	\$215	\$245	\$305
Oil-rubbed Bronze 11	N/A	N/A	\$420
Matte Black 19 Satin Brass 18	\$275	\$305	N/A
If Required by Construction Code			
Brass drain & overflow kit‡ BDRCOB		\$250	
Brass drain kit [‡] BDRCB		\$65	
16" x 35" Cable driven brass drain & overflow	kit BOVERBR	\$250	



https://bainultra.com/sites/default/files/product_files/product_sheet-amma-6036.pdf

1800 463-2187


 [†] ZenFlow: Integrated overflow without a trim.
 ** The AromaCloud® is built into the deck (factory installed).
 [‡] When ordered with Integrated drain & overflow.







Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	8 ½"
В	Outside edge to overflow	2 1/2"
С	Total length	60"
D	Total width	36"
E	Bathing well length	46"
F	Bathing well width at center zone	17 1/s"
G	Raised seat length	20"
Н	Raised seat width	20 %"
I	Deck width (narrowest point)	3 1/8"
J	Deck width (widest point)	4 1/8"
K	Deck width at drain end	2"
L	Total height to headrest	23 1/4"
М	Height from bottom of bath to top deck	21"
N	Height from bottom of bath to bottom of deck	19 ½"
0	Height from bottom of drain to center of overflow	17 1/s"
P	Maximum water level (Drain & overflow 16" x 35") Maximum water level (Integrated drain & overflow)	15 3/8" 16 3/8"
	Slope of backrest	18°

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated It must be connected to the hot water supply and be accessible (provide access).
	Optional Tile Flange (specify right or left).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Approx. shipping weight	142 lb
Turbine power	550 W
Air heater	600 W

Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*} Some restrictions apply | www.bainultra.com/warranty