elegancia 6642

66" x 42" x 21"



Product No.

Model C10	TMU BELNRDAOT-XX	Soaker BELNRDAON-XX
Model C11	TMU BELNODBOT-XX	Soaker BELNODBON-XX

Model C13	TMU BELNODDOT-XX	Soaker BELNODDON-XX
Model C14	TMU BELNODEOT-XX	Soaker BELNODEON-XX

ThermoMasseur (TMU)

Air Jet System	\$6,780
Jets	38
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$520
Geysair®	Included
AromaCloud® BAROMAC	\$620
Illuzio Chromatherapy BCHRO6	\$1,045
2nd heated backrest (WTS-1 zone) BSHB	\$1,180

Soaker	\$3,365
AromaCloud® BAROMAC	\$620
Illuzio Chromatherapy BCHRO6	\$1,045
WarmTouchShell® BWTS	\$1,180
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$390

Features

· oataroo		
Installation Type	Drop-in	
No. of bathers 👬 Imp. gallons 4 Grab bars (color match) 2	4 US gallons 53 Armrests 4	
Standard Bath Color		
White 01 Biscuit 02	Included	

1800463-2187

Options UPCHARGE APPLICABLE

Grab Bars	BGBG10-XX	Clear Acrylic [∞]	
Chrome 07		\$65	
Brushed Nickel 09		\$65	
Bath Pillow BPILLOW		\$250	
Comfort Cushion BCUSHIONA		\$565	
■ Grey 05 ■ Black 06			
Drain & Overflow		D13 BOVERD13-XX	D14 ⁺⁺⁺ BOVERD14-XX
Chrome 07		\$525	\$285
White 01		N/A	\$285
Biscuit 02		N/A	\$285
Brushed Nickel 09		\$525	\$285
Polished Nickel 10		\$525	\$285
Oil-rubbed Bronze 11		\$525	N/A
Matte Black 19 Satin Brass 18		N/A	N/A
Unplated 00		\$525	N/A

• Don't forget to select a contour among the 4 available to choose from.



https://bainultra.com/sites/default/files/product_files/product_sheet-elegancia-6642.pdf


 [†] ZenFlow: Integrated overflow without a trim.
[⋄] Specify insert finish. With Chrome or Brushed Nickel inserts.
^{‡†} Piping is not included for the drain & overflow D14.

elegancia 6642






Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	12 1/2"
В	Outside edge to overflow	6 ½"
С	Total length	66"
D	Total width	42"
E	Bathing well length	41 3/4"
F	Bathing well width	25 %"
G	Deck width (widest point)	6 1/8"
Н	Deck width at backrest end	4 3/4"
I	Height from bottom of drain to center of overflow	16"
J	Maximum water level (Drain & overflow 16" x 35")	14 5/16"
K	Slope of backrests	30°
Arom	aCloud® position	-installed (Mia® or DOT)

◆ Turbine position (TMU)
◆ Indicates heated backrest (TMU)
◆ Indicates WarmTouchShell
◆ position (Soaker)

Choose Your Contour



Letter	M	N	0
Description	Deck width (Narrowest point)	Height from bottom of bath to top deck	Height from bottom of bath to bottom of deck
C10	2 1/8"	20 ¾"	18"
C11	3 1/4"	20 %"	17 1/8"
C13	2 5/8"	20 %"	18 5/8"
C14	2 3/4"	20 ¾"	18"

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Gevsair® is located on the same side as the heated backrest. It must not be relocated

It must be connected to the hot water supply and be accessible (provide access). Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000043 (C11, C13 & C14)
Approx. shipping weight	140 lb
Turbine power	550 W
Air heater	600 W

Warranty Controls-LED-Geysair* 5 years Bath & turbine* 20 years

^{*} Some restrictions apply | www.bainultra.com/warranty