

inua 6036

60" x 36" x 23"



Slim deck ½"

Product No.

Model	Standard 1½" deck	TMU	BINFRD00T-XX	Soaker	BINFRD00N-XX
Model	Slim deck ½"	TMU	BINFRD10T-XX	Soaker	BINFRD10N-XX

ThermoMasseur (TMU)

Air Jet System	\$8,325
Jets	46
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application <i>BUTOUCH</i>	\$520
Geysair®	Included
AromaCloud® <i>BAROMAC</i>	\$620
AromaFlow™ <i>BAROMAF</i>	\$1,000
Illuzio Chromatherapy <i>BCHRO6</i>	\$1,045

Soaker

AromaCloud® <i>BAROMAC</i>	\$620
AromaFlow™ <i>BAROMAF</i>	\$1,000
Illuzio Chromatherapy <i>BCHRO6</i>	\$1,045
WarmTouchShell® <i>BWTS</i>	\$1,180
DOT Control	Included with therapy

Features

Installation Type	Drop-in
No. of bathers	2
Imp. gallons	45
US gallons	54
Raised seat	1
Inverted V	1
Armrests	2
Grab bars (Color match)	2
One Comfort Cushion (Specify color: Grey or Black)	1 Included
Standard Bath Color	
White 01	Included
Biscuit 02	

Options UPCHARGE APPLICABLE

Finish			
UltraVelour Matte Finish (white only) <i>BVEL1</i>			\$685
Clear Acrylic Grab Bars <i>BGBG10-XX</i>			
Chrome 07	Brushed Nickel 09 inserts		\$65
Bath Pillow <i>BPILLOW</i>			\$250
Drain & Overflow	Integrated ZenFlow™ <i>BOVERINZF-XX</i>	Integrated with trim <i>BOVERIN-XX</i>	16" x 35" <i>BOVER16-XX</i>
Chrome 07		\$215	\$245
White 01	Biscuit 02	\$175	\$215
Brushed Nickel 09		\$215	\$245
Polished Nickel 10		\$215	\$245
Oil-rubbed Bronze 11		N/A	\$420
Matte Black 19	Satin Brass 18	\$275	\$305
Matte White 32		\$215	\$245
If Required by Construction Code			
Brass drain & overflow kit† <i>BDRCOB</i>			\$250
Brass drain kit† <i>BDRCB</i>			\$65
16" x 35" Cable driven brass drain & overflow kit <i>BOVERBR</i>			\$250

⚠ Don't forget to specify the deck height (½" or 1 ½").

Faucets should be installed on the most level portion of the deck surface.


† ZenFlow: Integrated overflow without a trim.  
‡ When ordering an AromaFlow, an Integrated drain & overflow is mandatory (Upcharge). Specify the finish of the drain.  
\* When ordered with Integrated drain & overflow.

# inua 6036

60" x 36" x 23"



## Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11 ¼"
B	Outside edge to overflow	4 ½"
C	Total length	60"
D	Total width	36"
E	Bathing well length	42 ¼"
F	Bathing well width at center zone	23"
G	Raised seat length	20 ½"
H	Deck width at backrest end	4 ⅞"
I	Deck width at drain end	4 ⅞"
J	Deck width	4"
K	Height from bottom of bath to top deck	23"
L	Total height to headrest	21"
M	Height from bottom of bath to bottom of standard deck	19 ½"
M'	Height from bottom of bath to bottom of slim deck	20 ½"
N	Height from bottom of drain to center of overflow	17 ⅞"
O	Maximum water level (Drain & overflow 16" x 35")	15 ¾"
	Maximum water level (Integrated drain & overflow)	16 ¾"
	Maximum water level with AromaFlow	15 ¾"
P	Slope of backrest	24°
Q	Minimum spout reach	8"
R	Slim deck minimum height	½"
S	Standard deck minimum height	1 ½"

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Therapeutic Comfort Cushion - INCLUDED	Made of ultraresistant urethane gel. Extremely comfortable and soft to the touch. Fully waterproof. Remarkably durable. Color available: Grey or Black.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).
	The water level may vary when an AromaFlow or an Integrated drain & overflow is installed.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations ([www.bainultra.com/dealers/dealer-documentation-and-catalog](http://www.bainultra.com/dealers/dealer-documentation-and-catalog)).

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ±0.25" (±0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.

Approx. shipping weight	137 lb
Turbine power	550 W
Air heater	600 W

## Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

\* Some restrictions apply | [www.bainultra.com/warranty](http://www.bainultra.com/warranty)