

THERMOMASSEUR® BATH	\$
TUB	\$

THERMOMASSEUR (TMU)		
Jets	40	
1 heated backrest	included	
MiaPlus® Control	included	
Geysair®	included	
AromaCloud®	\$	
Illuzio Chromatherapy NEW	\$	
2 nd heated backrest (advanced technology)	\$	

TUB (soaker)		
AromaCloud®	\$	
Illuzio Chromatherapy NEW	y NEW \$	
WarmTouchShell®	\$	
DOT control	included with therapy	
2 nd WarmTouchShell®	\$	

ŤŤ

59

Imp. gallons

COLOR	
Standard White Biscuit	
Optional Gray	\$
CONTROL (TMU ONLY)	
MiaMulti®	\$
WASTE & OVERFLOW	16" X 35"
Chrome	\$
White, Biscuit	\$
Brass	\$
Brushed nickel, Polished nickel & Oil-rubbed bronze	\$

DON'T FORGET TO INDICATE FLAT OR ROLLED DECK. * THE AROMACLOUD IS NOT AVAILABLE WITH UNDERMOUNT INSTALLATION.

OPTIONAL UPCHARGE APPLICABLE

BainUltra The quest for your wellness• www.bainultra.com

1	800 463.2187	9
ir	nfo@bainultra.co	m

Installation types

No. of bathers

US gallons

Drop-in & Undermount *

49

ELLIPSE 7240 72" X 40" X 21"

ACCESSORIES	(OPTIONAL)
-------------	------------

CUTTING TEMPLATE

9000001


OTHERS

There is a height difference for the rolled deck (see drawing Detail A). Available with flat deck or rolled deck.


\$

TOTAL PRICE


DROP-IN/UNDERMOUNT INSTALLATION



the AromaCloud is built into the deck (DOT control, standard location)



A



Available with flat or rolled deck.

TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.	
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option , a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum	

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4'' [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.

LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center waste	11 3/4"
в	Outside edge to overflow	4 7/8''
с	Total length	72''
D	Total width	40''
E	Bathing well length	46 1/8''
F	Bathing well width	24 3/4"
G	Deck width at backrest end	4 3/4"
н	Deck width	4 5/8"
I	Rolled deck width	5 3/8"
J	Height from bottom of tub to top deck	21"
к	Height from bottom of tub to top deck	22''
L	Height from bottom of tub to bottom of lip	19 1/2"
м	Height from bottom of lip to top deck	2 1/2"
N	Height from waste to center of overflow	16 5/8"
0	Maximum water level	14 7/8''
Р	Slope of backrest	27°

AromaCloud position Control position when factory-installed (Mia or Dot)

Turbine position (TMU)

Approx. shipping weight 128 lbs Turbine power 550 W Air heater 600 W

WarmTouchShell position

WARRANTY

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

*Some restrictions apply | www.bainultra.com/warranty

