## **ELEGANCIA** 6032

60" x 32" x 19"

With shapes and lines that take us back to the Victorian era, this collection transcends time, fitting right in with today's styles.



## PRODUCT NO. MODEL TUB Drop-in BELDRBC0T-XX BELDRBCON-XX BELDRBCLN-XX Alcove - Left BELDRBCLT-XX Alcove - Right BELDRBCRT-XX BELDRBCRN-XX

<b>THERMOMASSEUR (TMU)</b> Hydro-thermo massage • Air jet system	\$
Jets	
1 heated backrest	Include
MiaPlus® Control	Include
BU-Touch Control Application BUTOUCH	\$
Geysair®	Include
AromaCloud® BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$

<b>TUB</b> Soaker	\$
AromaCloud® BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
WarmTouchShell® BWTS	\$
DOT control	Included with therapy

FEATURES				
Installation type		Drop-in & Alcove (3 walls)		
No. of bathers	*	Imp. gallons		37
US gallons	45	Integrated tile flange		Included
STANDARD COLOR				
White 01 Biscuit 02				Included

OPTIONS (UPCHARGE APPLICABLE)				
WASTE & OVERFLOW	D13 BOVERD1		ВО	<b>D14*</b> VERD14-XX
Chrome 07	\$		\$	
White 01, Biscuit 02		N/A	\$	
Brushed Nickel 09, Polished Nickel 10	\$		\$	
Unplated 00, Oil-rubbed Bronze 11	\$			N/A
SKIRT		MULTIFIT SJ-1 BSMUL-XX BSJ1-XX		•
White 01, Biscuit 02		\$		\$

Don't forget that an integrated tile flange is available at no extra cost.

You must specify waste position.
\* Piping is not included for the waste & overflow D14.

TOTAL PRICE











Exclusive contour C12 for this size

## INSTALLATION









LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	8"
В	Outside edge to overflow	2 1/4"
С	Total length	60"
D	Total width	32"
E	Bathing well length	46 3/8"
F	Bathing well width	21"
G	Deck width	3 7/8"
Н	Deck width at backrest end (widest point)	3 3/8"
I	Height from bottom of bath to top deck	19 1/4"
J	Height from bottom of bath to top deck	19 1/4"
K	Height from bottom of bath to bottom of deck	17 3/4"
L	Tile flange height	1"
М	Height from drain to center of overflow	14 1/2"
N	Maximum water level	12 7/8"
0	Slope of backrest	30°

⚠ AromaCloud® position

Control position when factory-installed (Mia® or DOT)

Turbine position (TMU)

Indicates heated backrest (TMU)

Indicates WarmTouchShell® position (TUB)

TECHNICAL SP	PECIFICATIONS		
Hot water supply required	Should be 70% of water capacity of TUB or greater.	Approx. shipping weight	125 lbs
supply required	Access to the pump must be at least 18" x 22". <b>Standard connection is 20 A. 120 V, 60 hz</b> , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). <b>For any additional option, a second line is</b>	Turbine power	550 W
Turbine		Air heater	600 W
	needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	WARRANTY	
Others	The GEYSAIR must always be accessible and connected to the hot water supply (provide access).     There is a height difference for the integrated tile flange (see drawing Detail A).	Controls-LED-Geysair*	5 years
	- Available with or without integrated tile flange (specify right or left).	Bath & turbine*	20 years
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).		* Some restrictions apply   www.bainultr	a.com/warranty





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.