MERIDIAN 55

66" x 36" x 20"

Named after the meridians of our body—the paths along which our energy flows—the collection also brings to mind the meridian (or mid-point) of life with an invitation to relax and listen to your body and mind.



			I
MODEL	TMU	TUB	
	BMELRI00T-XX	BMELRI00N-XX	

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$5,490
Jets	42
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$430
Geysair®	Included
AromaCloud®* BAROMAC	\$490
AromaFlow** BAROMAF NEW	\$950
Illuzio Chromatherapy BCHRO6	\$925
2 nd heated backrest (WTS-1 zone) BSHB	\$1,125

TUB Soaker	\$2,775
AromaCloud®* BAROMAC	\$490
AromaFlow** BAROMAF NEW	\$950
Illuzio Chromatherapy BCHRO6	\$925
WarmTouchShell® BWTS	\$1,125
DOT control	Included with therapy
2 nd WarmTouchShell® BWTS2	\$370

FEATURES			
Installation type	Drop-in & Alcove (3 walls)		
No. of bathers	* *	Imp. gallons	39
US gallons	47		
STANDARD COLOR			
White 01 Biscuit 02			Included
wnite 01 Biscuit 02			

OPTIONS (UPCHARGE APPLICABLE)		
SKIRT	MULTIFIT BSMUL-XX	SJ-1 BSJ1-XX
White 01, Biscuit 02	\$600	\$715
TILE FLANGE (specify front or back)		
Ordered with bath (not installed) BTILEN		\$79
Factory-installed. Right BTILER, Left BTILEL, Special installation BTILEO		\$155
WASTE & OVERFLOW	16" x 35" BOVER16-XX	INTE- GRATED** BOVERIN-XX
Chrome 07	\$260	\$235
White 01, Biscuit 02	\$290	\$235
Brushed Nickel 09, Polished Nickel 10	\$400	\$235
Oil-rubbed Bronze 11	\$400	N/A
Matte Black 19, Satin Brass 18	N/A	\$355
IF REQUIRED BY CONSTRUCTION CODE		
16" x 35" Cable driven brass waste & overflow kit BOVERBR		\$240



- * The AromaCloud® is built into the deck (factory installed).
 ** Only when ordering an AromaFlow; an Integrated waste & overflow is mandatory (Upcharge). Specify the finish of the waste.







MERIDIAN 55

INSTALLATION

(A) When tile flange is added, the AromaCloud® will automatically be installed on the opposite side of the flange.





LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	11 3/8"
В	Outside edge to overflow	4 1/4"
С	Total length	65 1/2"
D	Total width	35 3/4"
E	Bathing well length	46 1/8"
F	Bathing well width	23 1/4"
G	Deck width at backrest end	4 3/8"
Н	Deck width	4"
I	Height from bottom of bath to top deck	20 1/4"
J	Height from bottom of bath to bottom of deck	18 3/4"
K	Height from bottom of drain to center of overflow	16 1/8"
L	Maximum water level (Waste & overflow 16" x 35") Maximum water level with AromaFlow	14 3/8" 14 1/4"
М	Slope of backrest	24°
N	Slope of backrest	15°

⚠ AromaCloud® position

ⓒ Control position when factory-installed (Mia® or DOT)

Turbine position (TMU)

Indicates heated backrest (TMU)

Indicates WarmTouchShell® position (TUB)

TECHNICAL SP	ECIFICATIONS		
Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Cutting template	# 9000007
supply required	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz , dedicated	Approx. shipping weight	127 lb
Turbine	line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is	Turbine power	550 W
	needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater	600 W
Others	 The Geysair® is located on the same side as the heated backrest. It must NOT be relocated. It must be connected to the hot water supply and be accessible (provide access). Optional tile flange (specify front or back). If ordered with an installed tile flange and a back drain, the control will be shipped separately. The water level will be lower when an AromaFlow is installed. 	WARRANTY	
		Controls-LED-Geysair*	5 years
		Bath & turbine*	20 years
	the installed by certified professionals only and according to our Owner's Manual as well as federal, docal building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).	* Some restrictions apply www.bainulti	ra.com/warranty

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.