ELLIPSE 6636

Named after the meridians of our body—the paths along which our energy flows—the collection also brings to mind the meridian (or mid-point) of life with an invitation to relax and listen to your body and mind.

PRODUCT NO.

MODEL	тми	TUB
Rolled deck	BMELOUM0T-XX	BMELOUM0N-XX
Flat deck	BMELOUN0T-XX	BMELOUN0N-XX
THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system		\$6,080
Jets		38
1 heated backrest		Included
MiaPlus® Control		Included
BU-Touch Control Application BUTOUCH		\$430
Geysair®		Included
AromaCloud®* BAROMAC		\$490
AromaFlow** BAROMAF NEW		\$950
Illuzio Chromatherapy BCHRO6		\$925
2 nd heated backrest (WTS-1 zone) BSHB		\$1,125

TUB Soaker	\$2,690
AromaCloud [®] * BAROMAC	\$490
AromaFlow** BAROMAF NEW	\$950
Illuzio Chromatherapy BCHRO6	\$925
WarmTouchShell® BWTS	\$1,125
DOT control	Included with therapy
2 nd WarmTouchShell [®] BWTS2	\$370

FEATURES			
Installation type			Drop-in
No. of bathers	* *	Imp. gallons	40
US gallons	48		
STANDARD COLOR			
White 01 Biscuit 02			Included

Flat deck

OPTIONS (UPCHARGE APPLICABLE)

WASTE & OVERFLOW	16" x 35" BOVER16-XX	INTE- GRATED** BOVERIN-XX
Chrome 07	\$260	\$235
White 01, Biscuit 02	\$290	\$235
Brushed Nickel 09, Polished Nickel 10	\$400	\$235
Oil-rubbed Bronze 11	\$400	N/A
Matte Black 19, Satin Brass 18	N/A	\$355
IF REQUIRED BY CONSTRUCTION CODE		
16" x 35" Cable driven brass waste & overflow kit BOVERBR		\$240

Don't forget to indicate flat or rolled deck.

* The AromaCloud[®] is built into the deck (factory installed). ** Only when ordering an AromaFlow; an Integrated waste & overflow is mandatory (Upcharge). Specify the finish of the waste.






ELLIPSE 6636

INSTALLATION

A For rolled deck: deck modified ۵ to host the AromaCloud® Е G ٠H ΑB C (A) With flat deck, the AromaCloud® is built into the deck









LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	11 1/2"
в	Outside edge to overflow	4 5/8"
с	Total length	66"
D	Total width	36"
E	Bathing well length	42 3/8"
F	Bathing well width	22 1/4"
G	Deck width at backrest end	4 3/8"
н	Flat surface width	4 1/4"
I	Rolled deck width	4 3/4"
J	Height from bottom of bath to top deck	21"
к	Height from bottom of bath to top deck	22"
L	Height from bottom of bath to bottom of deck	19 1/2"
м	Height from bottom of deck to top deck	2 1/2"
N	Height from bottom of drain to center of overflow	16 5/8"
0	Maximum water level (Waste & overflow 16" x 35") Maximum water level with AromaFlow	14 7/8" 14 3/8"
Р	Slope of backrest	25°

AromaCloud[®] position

Control position when factory-installed (Mia[®] or DOT)

Turbine position (TMU)

Indicates heated backrest (TMU)

Indicates WarmTouchShell[®] position (TUB)

TECHNICAL SPECIFICATIONS

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Cutting template	# 90000055
	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated	Approx. shipping weight	100 lb
Turbine	line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is	Turbine power	550 W
needed 15 A. 120 V,	needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater	600 W
Others It must be conner - There is a height of	 The Geysair[®] is located on the same side as the heated backrest. It must NOT be relocated. It must be connected to the hot water supply and be accessible (provide access). 	WARRANTY	
	 There is a height difference for the rolled deck (see drawing Detail A). The water level will be lower when an AromaFlow is installed. 	Controls-LED-Geysair*	5 years
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).		Bath & turbine*	20 years
		* Some restrictions apply www.bainultra	a.com/warranty

* Some restrictions apply | www.bainultra.com/warranty

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra* assumes no responsibility for preparatory work done prior to the product being on site.