60" x 30" x 21"



Product No.

Model 2" Deck	TMU BOOBRIOOT-XX	Soaker BOOBRIOON-XX
Model Slim deck 1/2"	TMU BOOBRUIOT-XX	Soaker BOOBRUION-XX

ThermoMasseur (TMU)

Air Jet System	\$5,725	
Jets	40	
1 heated backrest	Included	
MiaPlus® Control	Included	
BU-Touch Control Application BUTOUCH	\$495	
Geysair®	Included	
AromaCloud®** BAROMAC	\$590	
AromaFlow ^{††} BAROMAF	\$950	
Illuzio Chromatherapy BCHRO6	\$995	

Soaker	\$3,035
AromaCloud®** BAROMAC	\$590
AromaFlow ^{††} BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy

Features

i catules			
Installation Type	•		Drop-in: ½", 2" Alcove (3 walls): 2" & Undermount: ½"
No. of bathers 🟺	Imp. gallons 38	US gallons 46	
Standard Bath C	olor		
○ White 01 ○	Discuit 02		Included

1800 463-2187

Options UPCHARGE APPLICABLE

Finish			
UltraVelour Matte Finish (white only) B	/EL1	\$650	
Skirt (2" deck only)		Multifit BSMUL-XX	SJ-1 BSJ1-XX
White 01 Biscuit 02		\$695	\$715
Tile Flange (2" deck only, specify right or le	eft)		
Ordered with bath (not installed) BTILEN		\$79	
Factory-installed. Right BTILER, Left BTILE Special installation BTILEO	L,	\$155	
Bath Pillow BPILLOW		\$240	
Drain & Overflow	Integrated ZenFlow [†] BOVERINZF-XX	Integrated with trim BOVERIN-XX	16" x 35" BOVER16-XX
Chrome 07	\$205	\$235	\$260
─ White 01 ─ Biscuit 02	\$165	\$205	\$290
Brushed Nickel 09	\$205	\$235	\$290
Polished Nickel 10	\$205	\$235	\$290
Oil-rubbed Bronze 11	N/A	N/A	\$400
Matte Black 19 Satin Brass 18	\$260	\$290	N/A
Matte White 32	\$205	\$235	N/A
If Required by Construction Code			
Brass drain & overflow kit‡ BDRCOB		\$240	
Brass drain kit [‡] BDRCB		\$60	
16" x 35" Cable driven brass drain & overflow	w kit BOVERBR	\$240	

- ¶ The ½" slim deck is available for drop-in and undermount installation only.
- [†] ZenFlow: Integrated overflow without a trim.
 ** The AromaCloud® is built into the deck (factory installed).
 Not available for undermount installation.
- When ordered with Integrated drain & overflow.
 When ordering an AromaFlow, a ZenFlow is mandatory (Upcharge).
 Specify the finish of the drain.




https://bainultra.com/sites/default/files/product_files/product-sheet-origami-6030.pdf

origami 6030





Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11"
В	Outside edge to overflow	3 5/8"
С	Total length (with ½" deck height) Total length (with 2" deck height)	59 %" 60"
D	Total width (with ½" deck height) Total width (with 2" deck height)	29 %" 30"
E	Bathing well length	43 1/4"
F	Bathing well width	19 5/8"
G	Deck width	3 1/4"
Н	Deck width	3 1/4"
I	Height from bottom of bath to top deck	21"
J	Height from bottom of bath to bottom of deck	19"
K	Height from bottom of drain to center of overflow	15 %"
L	Maximum water level (Drain & overflow 16" x 35") Maximum water level (Integrated drain & overflow) Maximum water level with AromaFlow	13 7/8" 14 7/8" 14 3/8"
М	Slope of backrest	24°

- ♠ AromaCloud® position
 ♠ Control position when factory-installed (Mia® or DOT)
 ♠ Indicates heated backrest (TMU)
 ♠ Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).	
	Optional Tile Flange (specify right or left). The water level will vary when an AromaFlow or an Integrated drain & overflow is installed.	

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000097
Approx. shipping weight	128 lb
Turbine power	550 W
Air heater	600 W

Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*} Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ±0.25" (±0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.