## **IBE OVAL** 5830

58" x 30" x 21" (FREESTANDING)

Vibe is a collection of therapeutic bathtubs with minimalist and contemporary flair. The collection is perfect for urban city dwellers who want to bring value and refinement to smaller bathrooms.



## PRODUCT NO.

MODEL	тми	TUB	
Freestanding	BVIAOF00T-XX	BVIAOF00N-XX	

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$8,655
Jets	35
1 heated backrest	Included
MiaPlus® Control*	Included
BU-Touch Control Application BUTOUCH	\$430
Geysair®	Included
AromaFlow*** BAROMAF NEW	\$950
Illuzio Chromatherapy BCHRO6	\$925

<b>TUB</b> Soaker	\$6,430
AromaFlow*** BAROMAF NEW	\$950
Illuzio Chromatherapy BCHRO6	\$925
WarmTouchShell® BWTS	\$1,125
DOT control	Included with therapy

FEATURES				
Installation type			F	reestanding
No. of bathers	*	Imp. gallo	ns	34
US gallons	40			
INTEGRATED WASTE & OVERFLOW BOVERINI-XX				
White 01, Chrome 07, Brusl Polished Nickel 10, Matte UltraVelour finish 32		9,	Installe	d & Included
STANDARD COLOR				
White 01				Included

OPTIONS (UPCHARGE APPLICABLE)	
COLOR	
Black / White 66	\$475
FINISH	
UltraVelour Matte Finish (white only) BVEL2	\$850
UNIVERSAL ARMRESTS BGBGU-XX	
White 01	\$750
INTEGRATED WASTE & OVERFLOW BOVERINI-XX	
Matte Black 19, Satin Brass 18	\$120
ISLAND TUB DRAIN™**	
Island Tub Drain™ BISLDD	\$260
Cast Iron Island Tub Drain™ BISLDDCI	\$310
IF REQUIRED BY CONSTRUCTION CODE	
Brass waste & overflow kit BDRCOB	\$240
Brass waste kit BDRCB	\$60



- Don't forget to specify the **finish of the integrated waste & overflow.** 
  - \* Control must be wall-mounted. Faucets must be freestanding or wall-mounted. \*\* An Island Tub Drain™ is required when there is **no access under**

  - the bath.


    \*\*\* When ordering an AromaFlow, an Integrated waste & overflow is mandatory (Included). Specify the finish of the waste.














LETTER	DESCRIPTION	MEASURE
Α	Total length	58"
В	Total width	30"
С	Bathing well length	41 1/4"
D	Bathing well width	20 1/8"
E	Center of air intake to center of drain (front)	3 1/2"
F	Center of air intake to center of drain (side)	3 1/2"
G	Outer edge to center of drain	10 1/16"
Н	Total height	21"
I	Deck width at headrest	1 3/8"
J	Slope of backrest	26°
К	Base length	47"
L	Deck width	1 3/8"
М	Base width	24 1/4"
N	Maximum water level Maximum water level with AromaFlow	14 5/16" 12 3/4"
0	Minimum spout reach	5 3/4"

Indicates heated backrest (TMU)

Indicates WarmTouchShell® position (TUB)

TECHNICAL SP	ECIFICATIONS		
Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Cutting template	# 90000080
supply required	Access to the pump must be at least 18" x 22". <b>Standard connection is 20 A. 120 V, 60 Hz</b> , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). <b>For any additional option, a second line is</b>	Approx. shipping weight	225 lb
Turbine lin		Turbine power	550 W
	needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater	600 W
Others  It must be conn - Faucet must be - The turbine mus - Controls cannot	The Geysair® is located on the same side as the heated backrest. It must NOT be relocated. It must be connected to the hot water supply and be accessible (provide access).  Faucet must be freestanding or wall-mounted.  The turbine must be remotely installed.	WARRANTY	
		Controls-LED-Geysair*	5 years
	- Controls cannot be installed on the deck of the bath The water level will be lower when an AromaFlow is installed.	Bath & turbine*	20 years
	be installed by certified professionals only and according to our Owner's Manual as well as federal, d local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).	* Some restrictions apply   www.bainultra	a.com/warranty

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.