PRODUCT SHEET

MONARCH 6080

Monarch is a refined collection of therapeutic baths with distinctive Quartz deck surfaces, for a look that's noble and pure.



DESCRIPTION	Т	ΛU	τι	JB	
Standard (S)*	BMOBRB00T-XX		BMOBRB00N-XX		
Grand Luxury (GL)*	BMLBRB00T-XX		BMLBRB00N-XX		
THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system		GL \$			
Jets				37	
1 heated backrest				Included	
MiaPlus [®] Control (not installed)				Included	
BU-Touch Control Application BUTOUCH NEW			\$		
Geysair®				Included	
AromaCloud®			N/A		
Illuzio Chromatherapy BCHRO6			\$		
TUB Soaker	S	\$	GL \$		
AromaCloud®	AromaCloud®			N/A	
Illuzio Chromatherapy Bo	CHRO6		\$		
WarmTouchShell [®] BWTS			\$		
DOT control			Included with therapy		
FEATURES					
Installation type			Drop-in & /	Alcove (3 walls)	
No. of bathers	•	Imp. gallons		42	
US gallons	50				
INTEGRATED WASTE 8	OVERFLO		x		
White 01, Chrome 07, Bru	ushed Nickel	09, Polished	Nickel 10	Inst. & Incl.	
STANDARD COLOR (inner shell)					
White 01				Included	
QUARTZ DECK COLOR S* GL* BDM06030-XX BDML603					
Grey Noka 22 Expo 21	Jet Black 23	Lagos Blue 24	Included	Included	

OPTIONS (UPCHARGE APPLICABLE) S* GL* BDMO6030-XX BDML6030-XX QUARTZ DECK COLOR \$ \$ Quasar Light 25 \$ \$ Piatra Bianco Woodlands Grey 26 Drift 31 30 \$ \$ Statuario Maximus 29 FINISH (inner shell) \$ UltraVelour Matte Finish (White only) BVEL INTEGRATED WASTE & OVERFLOW BOVERINI-XX Matte Black 19, Black Chrome 12, Satin Brass 18 \$ WASTE & OVERFLOW 16" x 35" BOVER16-XX Chrome 07 \$ \$ White 01 Brushed Nickel 09, Polished Nickel 10, Oil-rubbed Bronze 11 \$ QUARTZ SKIRT 6018 (60" x 18 7/8") BSM6018-XX Grey Expo 21, Noka 22 \$ \$ Jet Black 23, Lagos Blue 24 Quasar Light 25 \$ \$ Piatra Grey 26, Bianco Drift 31, Woodlands 30 Statuario Maximus 29 \$ TILE FLANGE (specify right or left) Ordered with bath (not installed) BTILEN \$ Factory-installed. Right BTILER, Left BTILEL, \$ Special installation BTILEO IF REQUIRED BY CONSTRUCTION CODE Brass waste & overflow kit** BDRCOB \$

\$

\$

BainUltra

16" x 35" Cable driven brass waste & overflow kit BOVERBR-XX


Brass waste kit** BDRCB







MONARCH 6030

INSTALLATION







LETTER	DESCRIPTION	MEASURE
А	Total length	60"
В	Total width	30"
с	Bathing well length (at height of jets)	43 5/8″
D	Bathing well width (at height of jets)	19 5/8″
E	Deck width (edges)	4″
F	Deck width (sides)	3 5/8″
G	Bath height	19 7/8″
н	Height from drain to center of overflow	15 3/8"
I	Outside edge to center drain	11 1/8″
J	Slope of backrest	24°
к	Quartz deck height	3/4″

Turbine position (TMU)
Indicates heated backrest (TMU)

\$

Indicates WarmTouchShell® position (TUB)

Don't forget that this model is available in White only with choice of quartz deck color. Don't forget to specify the finish of the integrated waste & overflow.

* Standard: Quartz deck with seam. Grand Luxury: one piece Quartz deck. ** When ordered with integrated waste & overflow.

TOTAL PRICE

TECHNICAL SP	ECIFICATIONS	
Hot water supply required	Should be 70% of water capacity of TUB or greater.	Approx. shipping weight
supply required	Assess to the sume must be at least 19// 20// Standard connection in 20 A 120 V C0 by dedicated	Turbine power
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 hz, dedicated line with a GFCI.	Air heater
		WARRANTY
Others	The GEYSAIR must always be accessible and connected to the hot water supply (provide access). Control cannot be installed on the Quartz deck.	Controls-LED-Geysair*
	- Optional tile flange (specify right or left).	Quartz deck*
Our products must be installed by certified professionals only and according to our Monarch Installation Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).		Bath & turbine*

* Some restrictions apply | www.bainultra.com/warranty



The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra* assumes no responsibility for preparatory work done prior to the product being on site.

226 lbs 550 W 600 W

5 years 15 years 20 years